



OPAL SO3700/TC/DP - 8/30W

LED Oyster 8 to 30 watt with selectable colour temperature and dual power

Application

A perfect choice for apartments or commercial spaces

Design Specifications

- Select colour temperature with DIP switch 3000K / 4000K / 6000K
- Durable powder coated steel body profile with a high performance opal PMMA diffuser
- High efficiency SMD LED chips, CRI > 80
- Integral constant current non-dimmable LED driver
- Integral dual power selection for DP models
- Two versatile profile sizes 8/16 or 15/30 watt, Microwave sensor optional to order.



Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V, DALI / DSI**
- In Built Sensor - **OPTIONAL**

Technical Specification

Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
SO3700/30/TC/DP	240	8/16	1200/1360/1280	3000/4000/6000	80	120
SO3700/40/TC/DP	240	15/30	2250/2550/2400	3000/4000/6000	80	120

Body Colour	Dim (mm)	Diameter (mm)
White	310(W) x 100(H)	390
White	390(W) x 112(H)	

Note: Lumens (lm) values shown are at full power rating

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Photometric Data

Unit: cd C0/C180 _____ C90/C270 _____

SO3700/30L/TC/DP at 4000K

SO3700/40L/TC/DP at 4000K

