



ECOLINE III SL9732TC - 10W/50W

LED narrow diffused batten with selectable CCT and Dual Power

Application

Conventional linear LED batten products for commercial service spaces

Design Specifications

- 65 mm narrow steel body
- White powder coat finish with a robust polycarbonate diffuser
- Large terminal block, easy installation
- Selectable CCT 3000K/4000K/5700K
- High efficiency LED optics, CRI >80, 120° beam distribution
- Integral LED driver with selectable power, Emergency options available and Non-dimmable corridorSTANDBY options available














Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **refer model no, Trailing edge, 1-10V, DALI / DSI**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**





Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Multiple Wattage	Lumens (lm)	CCT (K)
	SL9732/20TC/DP3	240		10/20	2370/2600/2460	3000/4000/5700
	SL9732/40TC/DP3	240		20/40	4600/5100/4860	3000/4000/5700
	SL9732/50TC/DP3	240		25/50	6100/6700/6300	3000/4000/5700
	SL9732/20TC/DP3EM	240		10/20	2370/2600/2460	3000/4000/5700
	SL9732/40TC/DP3/EM	240		24/40	4880/5340/5070	3000/4000/5700
	SL9732/50TC/DP3EM	240		25/50	6100/6700/6300	3000/4000/5700
	SL9732/20TC/DP3S	240		10/20	2370/2600/2460	3000/4000/5700
	SL9732/40TC/DP3S	240		20/40	4600/5100/4860	3000/4000/5700
	SL9732/20TC3DIM	240	20		2400/2500/2450	3000/4000/5700
	SL9732/40TC3DIM	240	40		4650/4900/4700	3000/4000/5700
	SL9732/50TC3DIM	240	40		4650/4900/4700	3000/4000/5700


CRI	Beam Angle (°)	Dimmable	Dim (mm)	Body Colour
80	120	NO	600(L) x 65(W) x 65(H)	WHITE
80	120	NO	1135(L) x 65(W) x 65(H)	WHITE
80	120	NO	1455(L) x 65(W) x 65(H)	WHITE
80	120	NO	600(L) x 65(W) x 65(H)	WHITE
80	120	NO	1135(L) x 65(W) x 65(H)	WHITE
80	120	NO	1455(L) x 65(W) x 65(H)	WHITE
80	120	NO	600(L) x 65(W) x 65(H)	WHITE
80	120	NO	1135(L) x 65(W) x 65(H)	WHITE
80	120	YES	600(L) x 65(W) x 65(H)	WHITE
80	120	YES	1135(L) x 65(W) x 65(H)	WHITE
80	120	YES	1455(L) x 65(W) x 65(H)	WHITE

NOTE: lumens (lm) shown are at FULL power setting

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL9732 20



SL9732 40

