



LED MULTI TRACK LIGHT STR4886MPTC - 30W /40W


Decorative three circuit, rotatable LED track light, with multi-focus adjustments, selectable CCT and power.

Application

Designed for decorative residential, retail and commercial applications

Design Specifications

- Extruded aluminium profile, horizontal 350° rotation, 90° vertical tilt
- White or black powder coated finish
- High output LED optics, CRI>90, CCT selectable 2700K / 4000K / 6000K
- Adjustable beam distribution, 24° - 60°
- Integral constant current non-dimmable, selectable power.



Performance

- Dimmable - NO

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Body Colour
	STR4886MP30TC/WH	240	20/25/30	2100/2300/2250	2700/4000/6000	WHITE
	STR4886MP30TC/BK	240	20/25/30	2100/2300/2250	2700/4000/6000	BLACK
	STR4886MP40TC/WH	240	30/35/40	3150/3400/3300	2700/4000/6000	WHITE
	STR4886MP40TC/BK	240	30/35/40	3150/3400/3300	2700/4000/6000	BLACK

CRI	Dim (mm)
90	170(L) x 72(W) x 210(H)
90	170(L) x 72(W) x 210(H)
90	170(L) x 80(W) x 250(H)
90	170(L) x 80(W) x 250(H)




Note: Lumens (lm) displayed are at the maximum power selection.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

WHO NEEDS AN OLD TIMER CONTROL.

PIXIE SMART GPO IS SMARTER THAN THE REST.

MULTIFUNCTION
CONTROL



For more
information
please
scan me

