



## SOL SL9726TC/EM - 20/50W

MAINTAINED OR NON-MAINTAINED, premium, IP65 LED weatherproof batten with selectable CCT and power

### Application

Commercial or industrial utility applications requiring IP65 and IK08 performance

### Design Specifications

- Selectable power and CCT 3000/4000/6000K
- Vandal resistant design, robust PC body, UV stabilized polycarbonate diffuser, fitted stainless steel clips & screws
- Integral non-dimmable LED driver
- Optional (non-dim) corridorSTANDBY function available for 40 watt EM
- Compliant to AS/NZS2293 Emergency Lighting & Exit Signs, guaranteed minimum 90 minutes emergency mode function with LiFePO4 battery technology. Emergency classification (20w) D32@C0, D25@C90, (40w) D40@C0, D40@C90, (50w) D50@C0, D40@C90
- Accessories included - PVC cable glands and suspension brackets. Installation types - Surface mount (standard) or if Suspended (a suspension kit is required). DALI option available.



### Technical Specification

| Product | Model No.      | Input Voltage (V/AC) | Multiple Wattage | Lumens (lm)    | CRI | Body Colour |
|---------|----------------|----------------------|------------------|----------------|-----|-------------|
|         | SL9726/20TC/EM | 240                  | 10/20            | 2040/2300/2200 | 80  | GREY        |
|         | SL9726/40TC/EM | 240                  | 20/42            | 4370/4990/4720 | 80  | GREY        |
|         | SL9726/50TC/EM | 240                  | 30/50            | 5480/6070/5920 | 80  | GREY        |

| Dim (mm)                 | IPART | VEET |
|--------------------------|-------|------|
| 642(L) x 118(W) x 77(H)  | YES   | YES  |
| 1251(L) x 118(W) x 77(H) | YES   | YES  |
| 1551(L) x 118(W) x 77(H) |       |      |

**Important notes:** (1) Lumens (lm) shown are at full rated power (2) In the interest of transport and safety, emergency products are supplied with the battery disconnected. (3) In addition to specific emergency commissioning instructions, the battery **MUST** be connected at the time of installation. (4) Continual use in emergency mode greater than 240 hours without recharge, will result in battery failure and void battery warranty.


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Photometric Data


### Photometric Data (at maintained power)

Unit: cd C0/C180 — C30/C210  
cd C60/C240 — C90/C270

SL9726/20TC/EM at 3000K



SL9726/40TC/EM at 4000K





Blackwattle Bay NSW

Images courtesy of MKGS Construction & Paton Power

**The difference between Non-maintained and Maintained Emergency Lighting?** Non-Maintained lighting products are luminaires designed solely for emergency use and will only operate in an event where the mains supply power is interrupted. Maintained Emergency Lighting products are designed to be illuminated at all times, including an emergency event where the power is interrupted. Under both systems, the products must remain illuminated for a period of 90 minutes in accordance with AS/NZS2293 Emergency Lighting requirements.

