



**HIGH PERFORMANCE  
SMOKE ALARMS**

# DATA SHEET GT10RF

10 year sealed lithium battery  
wireless interconnected  
smoke alarm

- ✓ Split-spectrum sensor technology
- ✓ Test and silence features in one single button, silenced by a working infrared remote controller
- ✓ Loud sound output over 85 dB(A) at 3 meters
- ✓ Low quiescent current consumption
- ✓ Surface-mount device (SMD) circuit board design
- ✓ Low battery warning signal
- ✓ Sealed lithium battery, easy installation
- ✓ Wireless interconnected with maximum of 24 devices

## SYSTEM OVERVIEW

Wireless Interconnected Smoke Alarm (hereinafter referred to as the device) is designed to continuously monitor smoke concentration. Adopting new split-spectrum sensor and a built-in high-volume buzzer, it responds quickly and becomes highly sensitive with stable performance and low false alarm. Once the surrounding smoke concentration reaches the alarm value, it will promptly send out visual and audible alarm signal to remind the user to take immediate measures. Moreover, the alarm signal will be pushed to every alarms in the interconnected network and they will raise the alarm in unison.



## SCENE

The device can be widely used in residential areas such as villas, apartments and dorms, including reading rooms, living rooms, bedrooms and hallways.

## TECHNICAL SPECIFICATION

### Working Principle

Collection Type	Smoke
Sampling Period	9 s
Sensor Type	Photoelectric

### Alarm

Alarm Type	Smoke alarm, fault warning, low battery warning
Alarm Volume	≥ 85dB (A) at 3 m (9.84 ft)
Alarm Mode	Visual and audible alarm
Silencing Function	Yes
Silence Duration	9 min
Infrared Silence	Yes
Pre-Set Alarm Value	0.2dB/m-0.3dB/m

## TECHNICAL SPECIFICATION

### Basic Parameters

Indicator Light	Alarm, fault and operation indicator
LED Instructions	Standby: Green indicator flashes once per minute Alarm: Red indicator flashes once per second Fault: Red indicator flashes twice per minute
Operating Frequency	925MHZ
Radio Signal Range	Up to 1000 m (3280.84 ft) in open air
Maximum Number of Interconnected Units	24pcs
Coverage Area	When the height of the space is less than 8 m (26.25 ft), the protection area of a device is 20 m <sup>2</sup> -40 m <sup>2</sup>

### Power Supply

Battery Life	10 years
Power Source	3V CR123A lithium battery (non-replaceable)
Operating Current	Monitoring current: ≤ 15uA (avg.) Alarm current: ≤ 35mA (avg.)

### Operating Ambient

Operating Environment	Indoor
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Operating Humidity	≤ 95% RH (non condensing)

### Appearance

Color	White
Casing	PC+ABS
Dimensions	φ81.5 mm × H51.6 mm (φ3.21" × H2.03")
Weight	110 g (0.24 lb)
Installation	Ceiling Mount


### Certification

Certifications	RCM
Compliance Standard	AS 3786:2014

## ORDERING INFORMATION

Type	Model Number	Description
Smoke Alarm	GT10RF	10 year sealed lithium battery wireless interconnected smoke alarm

## INSTALLATION



## DIMENSIONS (MM/INCH)

