



## SALRAY 3000TC - SSIF3000TC

IP65 LED SOLAR floodlight - 3000 lumens with selectable CCT

### Application

A sustainable floodlight solution for residential exterior spaces

### Design Specifications

- Robust black die-cast aluminium body, tempered glass diffuser and a versatile angled bracket for easy installation
- High efficiency LED optics, 3000 lumens, CRI 80, on-board selectable CCT, beam distribution 120°
- Lithium battery technology, with overcharge, over-discharge, load short circuit protection, non-dimmable integral driver
- PIR and dusk to dawn control
- Detection range 110°, max 4-6m, installation height max 2.5hm, hold time 25 sec, daylight threshold 20-30 lux, charge time 9 hours
- Mode settings: The default factory sensor MODE 1 setting is dusk to dawn with 100% PIR sensor control. If other MODE settings are required, in addition to the on-board button selections located on the rear of the luminaire, an optional remote controller is sold separately, refer installation instructions for settings.



### Performance

- Dimmable - **NO**
- In Built Sensor - **YES**
- Sensor Type - **PIR DUSK TO DAWN**



### Technical Specification

Model No.	Power (W)	Colour Temp. (K)	Lumens (lm)	CRI	Mass (kg)	Sensor Type
	17.5	3000	3000	80	0.7	PIR DUSK TO DAWN
						PIR DUSK TO DAWN

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".